

High Performance Industrial Thermal Solutions



M84Pro Series Printers

The *Pro* Series high-performance industrial printers are ideal for a range of applications, including:

-  **PCB Labeling**
-  **Component Marking**
-  **Ticketing**
-  **Retail Labeling**
-  **Compliance Labeling**
-  **Shipping/Receiving**
-  **Asset Tracking**
-  **WMS**

Heavy Duty Metal Construction

The *Pro* Series' rugged all-metal design makes these printers ideal for heavy-duty use in the harshest environments. The metal enclosure provides full protection of the print mechanism and media in any mission-critical application.

High Speed and Performance

The M84Pro uses the latest technology to provide maximum performance and eliminate wait time. The powerful RISC CPU delivers print speed of up to 10 inches (25.4 cm) per second, enabling you to generate the most complex label formats quickly and efficiently.


User Configurable Print Resolution

The *Pro* Series printers offer superior print quality at 203, 305, and 609 dpi. By simply changing the print head, you can quickly convert the M84Pro to any of three available print resolutions.



Performs best with
Techno
T H E R M
Labels & Ribbons

SPECIFICATIONS



Printing Method
Print Resolution
Print Speed
Media Width
Max. Print Width
Min. Print Length
Max. Print Length
Max. Ribbon Size
Dimensions
Weight

M84Pro(2)	M84Pro(3)	M84Pro(6)
Thermal Transfer/Direct Thermal		
203 dpi (8 dpmm)	305 dpi (12 dpmm)	609 dpi (24 dpmm)
10 ips (254 mm/s)	8 ips (200 mm/s)	6 ips (150 mm/s)
Max. 5" (128 mm) / Min. 0.87" (22 mm)		
4.1" (104 mm)		
0.24" (6 mm) - continuous / 0.63" (16 mm) - tear off / 1.18" (30 mm) - cutter/dispenser		
49.2" (1249 mm)	32.8" (833 mm)	14" (356 mm)
4.4" (111 mm) W x 1475' (450 m) L - Face-In		
10.4" (265 mm) W x 17.1" (435 mm) D x 13.4" (341 mm) H		
39.7 lbs (18 kg)		

Memory:

16 MB Standard RAM
 2 MB Standard Flash
 4 MB Flash - Optional
 1 MB or 256k PCMCIA - Optional

Processor:

32-BIT RISC

Media:

Roll-fed or fan-fold, die-cut or continuous direct thermal (thermal transfer) labels, synthetics, and tag stock with or without black mark, gap, or notch.

Max. Caliper: 0.01" (0.25 mm)
 Max. Roll Diameter: 8.6" (218 mm)
 Wind: Face-In

Sensing:

- Adjustable transmissive sensor for gap
- Reflective sensor for black mark
- Automatic, programmable top of form
- Label present sensor (opt. w/dispenser)
- Ribbon-out sensor

Plug-In Interface Modules:

- Serial - RS232 (up to 57.6k bps)
- Parallel - IEEE1284 (ECP)
- Ethernet - 10/100BaseT
- Wireless 802.11g
- Twinax/Coax
- RS422/485
- USB (Factory Installed)

Barcode Symbolologies:

Linear: UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet™, GS1-128, GS1-DataBar™

2-Dimensional: PDF417, Micro PDF417, Truncated PDF417, Maxicode™, Data Matrix, QR Code, Composite Symbolology

Fonts:

- Bitmap - 12 proportional, mono-spaced and outline fonts (Code table 858)
- Scalable Internal CG Triumvirate® and CG Times® fonts
- Optional Downloaded TrueType® fonts, scalable from 8 to 72 points

Barcode and Font Formatting:

- 360° rotation of barcodes and text
- Horizontal and vertical character expansion
- Sequential numbering
- Form overlay for high-speed editing of complex formats

Graphic Support:

Printing and storage of *.PCX, *.BMP format, SATO Hex/binary

Software:

- Windows® Drivers (Windows® 2000, XP, 2003, Vista and Windows 7)
- Label Software (*Label Gallery Free*)
- Printer Utilities

Electrical Requirements:

115V/220V (± 10%), 50/60 Hz (± 1%)
 (Jumper switch required)

Agency Certifications:

CE, UL, CSA, TÜV

Environmental Requirements:

Operating: 41° to 104°F (5° to 40°C)
 15-85% RH, non-condensing
 Storage: 23° to 140°F (-5° to 60°C)
 Max. 90% RH, non-condensing
 EDS: 8kV

Optional Features:


- Label Cutter
- Label Rewinder
- Real Time Clock
- Label Gallery
- Label Dispenser
- Memory Expansion
- Plug-In Interface



Memory Expansion



Plug-In Interface Modules



Printheads



Rewinder

SATO America, Inc.

Main Office

10350-A Nations Ford Road
 Charlotte, NC 28273
 Phone: (704) 644-1650
 Fax: (704) 644-1662
 sato-sales@satoamerica.com

Romeoville Office

1140 Windham Parkway
 Romeoville, IL 60446
 Phone: (630) 771-4200
 Fax: (630) 771-4210
 retail@satoamerica.com

Horticultural Division

930 Jimmy Ann Drive
 Daytona Beach, FL 32117
 Phone: (386) 274-5566
 Fax: (386) 274-5599
 hort@satoamerica.com

©2013 SATO America, Inc. All rights Reserved. Rev C • Specifications subject to change without notice • Any unauthorized reproduction of the contents of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.